

Amendments to the Claims

This listing of claims will replace all prior listings of claims in the application.

Listing of Claims

1. (Currently Amended) A method for generating 3-dimensional computer images comprising the steps of:

- a) subdividing the image into a plurality of rectangular areas;
- b) loading object data for each rectangular area into a display list memory until that memory is substantially full;
- c) deriving image data and shading data for each picture element of each rectangular area from the object data;
- d) storing the image data and the shading data in a local memory;
- e) loading further object data into the display list memory to replace the existing contents;
- f) retrieving the stored image data and shading data;
- g) deriving additional image data and shading data for each picture element of each rectangular area from the new object data and the previously derived image data and shading data;
- h) repeating steps d), e), f) and g) until there is no further object data to load to the display list memory; and
- i) providing the shading data to a frame buffer memory for display.

2. (Original) A method according to claim 1 in which the image data comprises object identification data and depth data.

3. (Previously Presented) A method according to claim 1 including the steps of compressing the image data prior to

step d) and decompressing the compressed image data prior to step g).

4. (Previously Presented) Apparatus for generating 3-dimensional computer images comprising:

- a) means for subdividing the image into a plurality of rectangular areas;
- b) means for loading object data for each rectangular area into a display list memory until the memory is substantially full;
- c) means for deriving image data and shading data for each picture element of each rectangular area from the object data;
- d) means for storing the image data and shading data for each rectangular area;
- e) means for loading further object data into the display list memory to reduce the existing contents;
- f) means for retrieving the stored image data and shading data;
- g) means for deriving further image data shading data for each picture element of each rectangular area from the new object data and the stored image data and shading data;
- h) means for causing features d), e), f) and g) to repeatedly perform the functions until there is no further object data to load to the display list memory; and
- i) providing the shading data for display.

5. (Original) Apparatus according to claim 4 in which the image data comprises object identification and depth data.

6. (Previously Presented) Apparatus according to claim 4 including means to compress the image data before it is stored and means to decompress the compressed image data after it is retrieved.

7. (Original) A memory management system for use with systems for generating 3-dimensional computer images comprising means for subdividing the image data into a plurality of substantially rectangular areas, means for storing data pertaining to surfaces making up the image in a display list memory, means for allocating at least one block of storage from the display list memory to each rectangular area and means for storing in that block of memory data pertaining to surfaces which intersect that rectangular area, means for supplying data for each rectangular area from the display list to a means for deriving shading data for each picture element of the rectangular area, and frame store means for storing the shading data for display characterised in that each rectangular area comprises a plurality of smaller rectangular areas and the means for deriving shading data derives the data for each smaller rectangular area in turn.

8. (Original) A memory management system according to claim 7 in which the means for allocating blocks of storage from the display list determines when a predetermined number of blocks have been used and, in dependence on the determination, causes the means for supplying data to the means for deriving shading data to commence operation, thereby releasing blocks of storage for further object data.

9. (Previously Presented) A memory management system according to claim 7 in which the image data comprises a sequence of frames of data.

10. (Original) A method for managing memory for a system for generating 3-dimensional computer images comprising the steps of subdividing the image into a plurality of rectangular areas, storing data pertaining to surfaces in the

image which intersect each rectangular area in a display list memory, allocating at least one block of the display list memory to each rectangular area, storing in that block data pertaining to surfaces intersecting the respective rectangular area, supplying data for each rectangular area to a shading means whereby shading data is derived from each picture element making up the rectangular area, and storing the shading data for display characterised in that the step of subdividing the image further comprises subdividing each rectangular area into a plurality of smaller rectangular areas and the shading means shades each smaller rectangular area in turn.

11. (Original) A method for managing memory according to claim 10 including the step of determining when a predetermined number of blocks of the display list memory have been allocated to rectangular areas, and commences the supply of data to the shading means in dependence on the determination, thereby releasing blocks of storage for further object data.

12. (Original) A memory management system for use with systems for generating 3-dimensional computer images comprising means for subdividing the image data into a plurality of substantially rectangular areas, means for storing data pertaining to surfaces making up the image in a display list memory, means for allocating at least one block of storage from the display list memory to each rectangular area, means for storing in that block of memory data pertaining to surfaces which intersect that rectangular area, means for supplying data for each rectangular area from the display list to a means for deriving shading data for each picture element of the rectangular area, and frame store means for storing the shading data for display, characterised in

that the means for allocating blocks of storage from the display list memory determines when a predetermined number of blocks have been used and, in dependence on the determination, causes the means for supplying data to the means for deriving shading data to commence operation, thereby releasing blocks of storage for further rectangular areas.

13. (Original) A method for managing memory for a system for generating 3-dimensional computer images comprising the steps of subdividing the image into a plurality of rectangular areas, storing data pertaining to surfaces in the image which intersect each rectangular area in a display list memory, allocating at least one block of the display list memory to each rectangular area storing in that block data pertaining to surfaces intersecting the respective rectangular area, supplying data for each rectangular area to a shading means whereby shading data is derived from each picture element making up the rectangular area, and storing the shading data for display, characterized by the step of determining when a predetermined number of blocks of the display list memory have been allocated to rectangular areas, and commencing the step of supplying data to the shading means in dependence on the determination, thereby releasing blocks of storage for further object data.

Claims 14 and 15 (Cancelled).

16. (New) A memory management system for use with systems for generating 3-dimensional computer images comprising:

means for subdividing image data into a plurality of substantially rectangular areas, with a predefined number of neighboring rectangular areas defining a macro-area;

a display list memory for storing data pertaining to surfaces making up the image, the display list memory being divided into portions corresponding to each of the defined macro-areas, with each portion comprising a plurality of storage blocks;

means for allocating at least one of the storage blocks of a selected portion of the display list memory to each rectangular area of the corresponding macro-area;

means for storing data concerning surfaces that intersect a specified rectangular area of the image into the at least one allocated storage block of the corresponding portion of the display list memory;

means for supplying, for each picture element of each rectangular area of each macro-area of the image, data from the display list memory to a means for deriving shading data; and

frame store means for storing the derived shading data for display.

17. (New) A method for managing memory in a system for generating 3-dimensional computer images, comprising the steps of:

subdividing image data into a plurality of substantially rectangular areas, with a predefined number of neighboring rectangular areas defining a macro-area;

storing data pertaining to surfaces making up the image into a display list memory, the display list memory being divided into portions corresponding to each of the defined macro-areas, with each portion comprising a plurality of storage blocks;

allocating at least one of the storage blocks of a selected portion of the display list memory to each rectangular area of the corresponding macro-area;

storing data concerning surfaces that intersect a specified rectangular area of the image into the at least one allocated storage block of the corresponding portion of the display list memory;

supplying data, for each picture element of each rectangular area of each macro-area of the image, from the display list memory to a means for deriving shading data; and

storing the derived shading data in a frame store for display.